

## News Release

Freising-Weihenstephan, 11 March 2011

**Making timber safer:**

### **TUM researchers recommend new EU standards for machine strength grading of engineered wood products**

**Be it in houses, halls, towers or bridges – timber is a versatile and environmentally friendly construction material. In order to ensure that wooden structures are sufficiently stable for their required purpose, the timber used must first be graded according to its strength. Reliable and fast machines to do this already exist, however they are rarely used in practice because current EU standards stipulate expensive acceptance requirements that vary according to timber type and growth area. That is why timber is usually classified visually – which is both slower and less accurate. Wood technologists from Technische Universität München (TUM) have now conducted an international project to find out how the obstacles to machine strength grading can be overcome. This should make timber a more competitive and, at the same time, safer construction material.**

The natural product wood grows in locations with different climate, soil and environmental conditions. These differences influence its properties as construction material: “Scandinavian spruce, for instance, has smaller knots and lower raw densities than spruce coming from central Europe, and this results in different strength and stiffness values,” explains Professor Jan-Willem van de Kuilen from the Department of Wood Technology at TUM. That is why, to ensure the stability of wooden structures, timber must be strength graded before it is used. So far, grading is predominantly visual, i.e. according to visible attributes influencing strength, e.g. the proportion of knots, which reduce wood stability, or discolorations indicative of fungi.

Machine strength grading is both more efficient and more reliable: It also includes criteria that are not visible, such as density or elasticity, and it works much faster than expert eyes. Nonetheless, machine grading of engineered wood products has not become established practice yet, because it is subject to stringent EU-wide standards – a machine may only sort timber of a certain type and from a specified growth area, for which it has been granted specific acceptance. When, for instance, a machine that has been officially accepted for grading German pine, is to be used for Polish pine, EU legislation stipulates that it first go through a lengthy and very costly series of tests measuring 450 samples of this specific

Technische Universität München    Corporate Communications Center    80290 München    [www.tum.de](http://www.tum.de)

Dr. Ulrich Marsch  
Jana Bodický M.A.

Head of Corporate Communications  
Media Relations

+49.89.289.22778  
+49.8161.71.5403

[marsch@zv.tum.de](mailto:marsch@zv.tum.de)  
[bodicky@zv.tum.de](mailto:bodicky@zv.tum.de)

timber. However, a sawmill often has to process timber from different growth areas in parallel, making machine strength grading uneconomical.

The Department of Wood Technology at TUM, together with international colleagues, tackled this challenge within the European research project “GRADEWOOD.” The researchers set out to establish the following: In how far does timber origin influence strength? Does the existing differentiation in EU norms according to country of origin even make sense? To answer these questions the TUM team spent two years in Germany, France, Belgium and Sweden grading over 6,000 timber specimens of spruce and pine from ten European countries. A great deal of work, considering that for every individual sample they had to use five machines to measure the different timber strength parameters. One approach was to get the timber to vibrate and then measure its natural frequency: the higher the natural frequency, the stronger the timber. After completing the series of tests, the TUM researchers measured the actual strengths of the timber samples. They did this by bending the samples until they broke – the force required, together with the thickness and width of the sample were used to calculate the strength of the timber.

When they compared the compiled data, the wood technologists were in for a surprise: Not all regional differences in timber strength were attributable to the measured parameters. For instance, their extensive experiments showed the density and elasticity of spruce from Poland and Sweden to be the same. Yet, the respective strengths turned out to be different. TUM project leader Peter Stapel from the Department of Wood Technology concludes: “There are parameters influencing timber properties that are yet to be established.” And so the search goes on – in a next step the wood researchers hope to find additional measurable parameters that can be used to increase the forecast accuracy of the timber grading machines.

There is, however, one important issue that the TUM researchers can already elucidate on clearly: Together with their international colleagues they successfully demonstrated that there are indeed differences in timber properties according to growth areas, albeit they are so small that it makes no sense to classify timber according to the country of origin. The scientists believe that a classification by three larger regions in which timber displays similar properties would be perfectly sufficient: Northern, Central and Eastern Europe. And this is what the researchers would like to propose to the European Committee for Standardization. This would facilitate machine grading of engineered wood products throughout Europe – and could, in future, translate not only into more reliable, faster and more cost-effective strength grading of timber, but also into higher safety in construction.

**Technische Universität München    Corporate Communications Center    80290 München    [www.tum.de](http://www.tum.de)**

Dr. Ulrich Marsch	Head of Corporate Communications	+49.89.289.22778	<a href="mailto:marsch@zv.tum.de">marsch@zv.tum.de</a>
Jana Bodický M.A.	Media Relations	+49.8161.71.5403	<a href="mailto:bodicky@zv.tum.de">bodicky@zv.tum.de</a>

**Contact:**

Technische Universität München  
Department of Wood Technology  
Prof. Jan-Willem van de Kuilen or Peter Stapel  
80797 München, Germany  
Tel.: +49 89 / 2180-6462 or -6352  
E-Mail: [vandekuilen@wzw.tum.de](mailto:vandekuilen@wzw.tum.de) or [stapel@wzw.tum.de](mailto:stapel@wzw.tum.de)  
<http://www.holz.wzw.tum.de>

**Event announcement for representatives of the press:**

The whole-day closing event of the international GRADEWOOD research team will take place on 17 March at 10 a.m. at the TUM Center of Life and Food Sciences Weihenstephan, lecture hall 21 (postal address: Hans-Carl-von-Carlowitz-Platz 2, 85354 Freising). The research groups will put forward the results of the project in different presentations. At the event the team of the TUM Department of Wood Technology will focus on the correlations between growth area and timber properties. Furthermore, industry representatives will elucidate the current state of technology for machine strength grading. If you wish to conduct interviews during the closing event, please contact the Press Office: [presse@wzw.tum.de](mailto:presse@wzw.tum.de)

**Event timetable:**

<http://portal.mytum.de/ccp/presse/fachveranstaltungen/EU-Holzsortierung.pdf/download>

**Background:**

“GRADEWOOD - Grading of timber for engineered wood products” is a subproject of the European WoodWisdom-Net Research Program. GRADEWOOD bundles nine research groups from eight EU countries, with the Technische Universität München as the only German project partner. Altogether 1.4 million euro are available for GRADEWOOD over the entire term of the project. The TUM researchers are being funded with 140,000 euro by the Federal Ministry of Education and Research until the end of August 2011. Further information on the project can be found at <http://www.nexdo.com/public?w=579&p=GRADEWOOD>, and on the whole WoodWisdom-Net Research Program at <http://www.woodwisdom.net/>

**Technische Universität München (TUM)** is one of Europe’s leading technical universities. It has roughly 460 professors, 7,500 academic and non-academic staff (including those at the university hospital “Rechts der Isar”), and 26,000 students. It focuses on the engineering sciences, natural sciences, life sciences, medicine, and economic sciences. After winning numerous awards, it was selected as an “Elite University” in 2006 by the Science Council (Wissenschaftsrat) and the German Research Foundation (DFG). The university’s global network includes an outpost in Singapore. TUM is dedicated to the ideal of a top-level research based entrepreneurial university.

**Technische Universität München    Corporate Communications Center    80290 München    [www.tum.de](http://www.tum.de)**

Dr. Ulrich Marsch	Head of Corporate Communications	+49.89.289.22778	<a href="mailto:marsch@zv.tum.de">marsch@zv.tum.de</a>
Jana Bodický M.A.	Media Relations	+49.8161.71.5403	<a href="mailto:bodicky@zv.tum.de">bodicky@zv.tum.de</a>